## Technical Data Sheet | Mounting Plate

PT3 Cable tray provides premium performance for commercial & light industrial electrical projects.

Strong, versatile & easy to install, its excellent performance characteristics combined with a visually appealing profile has made it the highest regarded tray product in the electrical industry.





## Horizontal Mounting Plate:

- Under Purlin Centre Mounting Plate.
- Thread is 2cm high from plate.
- Pack 50

 Size:
 M10
 Size:
 M12

 Load kN:
 3.19
 Load kN:
 4.69

 Code:
 10HMP10
 Code:
 10HMP12



## **Vertical Mounting Plate:**

- Pack 100

 Size:
 M10
 Size:
 M12

 Load kN: 4.01
 Load kN: 5.77

 Code:
 10VMP10
 Code: 10VMP12



## Side Mounting Plate:

- Pack 100

 Size:
 M10
 Size:
 M12

 Load kN:
 5.25
 Load kN:
 5.96

 Code:
 10SMP10
 Code:
 10SMP12

ZINC PLATING (ZP): 8-15 MICRON
STANDARDS TO COMPLY: AS/NIZS 4680 A

STANDARDS TO COMPLY: AS/NZS 4680, AS1397.

HOT DIP GALVANISING (HDG): 50-70 MICRON STANDARDS TO COMPLY: AS/NZS 4680, AS1397.

NOTE: LOAD RATING IS APPLICABLE ONLY IF LOAD BEARING CAPACITY OF SUPPORTING ELEMENT IS ADEQUATE



Call : 1300 303 366 sales@powagroup.com.au www.powaroup.com.au