

ARAX TOUCH GLOVE

PRODUCT CODE: APUD(SIZE)

FEATURES & BENEFITS

- EN388:2016 Cut Resistance Level "C".
- ASTM Cut Level 3.
- Contact heat resistant to 100°C.
- Good cut resistance without sacrificing comfort or dexterity.
- Water based polyurethane finish coated palm.
- Breathable Arax® liner.
- Form fitting for comfortable all day wear.
- Colour coded cuff for size identification.

APPLICATIONS

Metal Fabrication, Sheet Metal Handling, Glass/Tiles/Ceramics Handling, Rigging, Landscaping, Construction, Mining, Materials Handling, Demolition, Cut & Abrasion Risks

PRODUCT DETAILS

- Material** : Engineered Composite 15 Gauge Seamless Arax® Liner
- Dip** : Water based PU in Black
- Cuff Type** : Knitted
- Colour** : Blue Speckle
- Sizes** : 7, 8, 9, 10, 11
- Qty/Pack** : 12 pairs
- Qty/Carton** : 120 pairs

PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	GLOVE LENGTH
7	8.5cm +/-	21.5cm +/-
8	9.5cm +/-	22.5cm +/-
9	10.0cm +/-	23.5cm +/-
10	10.5cm +/-	24.5cm +/-
11	10.5cm +/-	25.5cm +/-

STANDARDS

CE CATEGORY:

II Intermediary risk in accordance with:

EN 420 / AS / NZS2161.2:2005 General Requirements

EN 388:2016 Protection Against Mechanical Risks

Results - 4X42C

EN 407 / AS / NZS2161.4:1999 Protection Against

Thermal Risks (Heat & Fire)

Results - X1XXXX

ASTM F1790 Cut Level

Results - 3



PRODUCT CODE: APUD(SIZE)



CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
A	<2	200gms
B	≥5	500gms
C	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg

www.prosafetygear.com

PERTH

T [618] 9301 7888
F [618] 9301 7889

E wa@paramountsafety.com.au

MELBOURNE

T [613] 9764 9900
F [613] 9764 9800

E vic@paramountsafety.com.au

SYDNEY

T [612] 9601 3877
F [612] 9601 3899

E nsw@paramountsafety.com.au

BRISBANE

T [617] 3806 2699
F [617] 3806 3266

E qld@paramountsafety.com.au

ADELAIDE

T [613] 9762 2500
F [613] 9762 3500
M 0424 504 802

E sa@paramountsafety.com.au

NEW ZEALAND

T [649] 525 8090
F [649] 523 9773

E nz@paramountsafety.co.nz