

# SLOTTED ANGLE Z/P



## PRODUCT DETAILS

Used for the installation of building services with punched slots to facilitate suspending with threaded rod. Commonly used for supporting ductwok.



## FINISH

Zinc Plated

50MM X 50MM X 5MM X 3 METER LENGTH

09AJANG003

| SPAN (mm)                       | 250  | 500 | 750 | 1000 | 1250 | 1500 | 1750 | 2000 | 2250 | 2500 | 2750 | 3000 |
|---------------------------------|------|-----|-----|------|------|------|------|------|------|------|------|------|
| Max. Allowable Uniform Load(KN) | 11.1 | 5.6 | 3.7 | 2.8  | 2.2  | 1.9  | 1.6  | 1.4  | 1.2  | 1.1  | 1.0  | 0.9  |

30MM X 30MM X 2.5MM X 3 METER LENGTH

09AJANG001

| SPAN (mm)                       | 250 | 500 | 750 | 1000 | 1250 | 1500 | 1750 | 2000 | 2250 | 2500 | 2750 | 3000 |
|---------------------------------|-----|-----|-----|------|------|------|------|------|------|------|------|------|
| Max. Allowable Uniform Load(KN) | 1.7 | 0.9 | 0.7 | 0.6  | 0.5  | 0.4  | 0.3  | 0.3  | 0.2  | 0.2  | 0.1  | 0.1  |